



Parasoleil

303.589.4524

hello@parasoleil.com

parasoleil.com

All Parasoleil patterns are protected under copyright © law. Copying, modifying, or any unauthorized use of these patterns is strictly prohibited.

PARASOLEIL DATA SHEET

PFL Series Bracket (flush mount hardware)

Parasoleil's standard hardware integrates engineered connections with an interchangeable design language and known manufacturing tolerances.

BENEFITS & FEATURES

- Prescribed spacing of fastening points with built-in tolerances for complete system installation
- Single-point mounting into all materials, with field tolerance
- Bracket aligns panel layout and maintains consistent panel spacing
- Corrosion resistant aluminum and stainless steel construction

SPECIFICATIONS

- 3/16" thick 5052 aluminum alloy
- Stainless steel flush mount 1/4"-20 x 1/2" long studs
- 70 in/lb max nut tightening torque
- Stainless steel cap nuts with EPDM washer

STRUCTURAL RECOMMENDATIONS

- 24" on center max. bracket spacing along panel edges
- Contact Parasoleil for additional guidelines for high loading conditions

FINISHES

- Graftone, Nimbus, Raven standard powdercoat finishes
- Anodized options may be available
- Custom finishes available

QUESTIONS?

Contact Parasoleil for complete specifications, installation requirements and warranty coverage.